



## Ram Pump Systems

### Reliable Delivery of Medium- to High-Viscosity Fluids Packaged in Pails

- Platin design minimizes leftover material and reduces waste
- Features a fluid control module for accurate monitoring and control of fluid pressure
- Integrated air controls for easy system operation and monitoring
- Integrated drum air blow-off allows for quicker material changeover with less downtime.
- Models available for tapered or straight pails.
- Compatible with a wide variety of pails, allowing more dispensing flexibility

The Dymax ram pail pump system uses a displacement pump to transfer medium- to high-viscosity fluids packaged in pails to the dispensing valve. The ram pail pump system is designed to dispense from a 5-gallon (20 L) pail and is available in two models to accommodate both straight and tapered pails. The system is designed with a platen that wipes the sides of the pail as the material level lowers. This wiping action minimizes leftover material and reduces waste, creating a more efficient dispensing process. The ram pail pump is easy to operate with integrated air controls and a fluid control module mounted directly to the system.

#### Specifications

<b>Part Numbers</b>	<a href="#">T21286-001</a> Ram Pail Pump with Straight Platen/Wiper <a href="#">T21286-002</a> Ram Pail Pump with Tapered Platen/Wiper
<b>Pail Size</b>	5 Gallon (20 L)
<b>Maximum Air Input Pressure</b>	125 psi
<b>Ambient Operating Temp. Range (Supply System)</b>	32-120°F (0-49°C)
<b>Max Weight for Platen</b>	19 lbs (8.7 kg)
<b>Replacement Parts</b>	<a href="#">T16715</a> Silicone Replacement Wiper <a href="#">T18460</a> Upper Bleed Purge Valve <a href="#">T18643</a> Throat Seal O-Ring Rebuild Kit <a href="#">T18467</a> Follower Plate O-Ring Seal <a href="#">T18612</a> Crossover Controls Kit



[www.dymax.com](http://www.dymax.com)

**Americas**

USA | +1.860.482.1010 | [info@dymax.com](mailto:info@dymax.com)

**Europe**

Germany | +49 611.962.7900 | [info\\_de@dymax.com](mailto:info_de@dymax.com)  
Ireland | +353 21.237.3016 | [info\\_ie@dymax.com](mailto:info_ie@dymax.com)

**Asia**

Singapore | +65.67522887 | [info\\_ap@dymax.com](mailto:info_ap@dymax.com)  
Shanghai | +86.21.37285759 | [dymaxasia@dymax.com](mailto:dymaxasia@dymax.com)  
Shenzhen | +86.755.83485759 | [dymaxasia@dymax.com](mailto:dymaxasia@dymax.com)  
Hong Kong | +852.2460.7038 | [dymaxasia@dymax.com](mailto:dymaxasia@dymax.com)  
Korea | +82.31.608.3434 | [info\\_kr@dymax.com](mailto:info_kr@dymax.com)